

## Technical Informations

Product : **Teak Deck Cleaner ( TDC) Liquid**

Date : **12 / 2018**

## Description

**Teak Deck Cleaner Liquid** has been formulated as a 2 in 1 product. It is an advanced cleaning liquid designed specifically for the yacht and marine industry. **TDC** is designed to not harm you, your teak, seam sealants, hardware or paint. It is a new concentrated solution which can be used in various dilutions, from concentrated direct from the can, to diluted in fresh water up to 1:20. **TDC Liquid** cleans and brightens teakwood, similar to harsh 2 part cleaners helping restore the original golden colour.

## Typical Benefits

- Concentrated Liquid, ready-to-use in various dilutions.
- Removes mold & mildew stains.
- Cleans & brightens.
- Tough on dirt, gentle on teak.
- Meets Global Marina Programs / MARPOL regulations for clean environment.

## Typical Properties

<b>Colour :</b>	yellowish
<b>Mixture</b>	1:1 to 1:20 With water
<b>Shelflife</b>	4 Years
<b>App. Temperatur</b>	+5 °C bis +40°C

## Directions for use

A teak deck caulked with **Tikalflex TSC** shall only be cleaned with **Saltwater/ or Tikal Teak Deck Cleaner (TDC) Liquid..**

### **For light cleaning:**

Pour **TDC** to a suitable bucket and dilute it maximum up to 1:20, make sure the bucket is large enough for easy access by your white scrub pad or soft deck brush.

Wet out the area of teak to be cleaned.

Apply **TDC** and lightly scrub the teak across the grain, never with the grain. Allow to soak for 10 minutes.

If applying in direct sun, rinse in a timely manner to avoid having the released dirt and solution dry. If surface starts to dry, apply more cleaner.

When rinsing, lightly brush the deck to help release the deep imbedded dirt. Thoroughly rinse the entire area with water and squeegee off excess.

### **For heavy cleaning:**

Pour **TDC** in full strength to a suitable bucket, make sure the bucket is large enough for easy access by your white scrub pad or soft deck brush.

Do not wet the area of teak to be cleaned.

Apply **TDC** and lightly scrub the teak across the grain, never with the grain. Allow to soak for 10 minutes.

If applying in direct sun, If surface starts to dry, apply more cleaner. When rinsing, lightly brush the deck to help release the deep imbedded dirt. Thoroughly rinse the entire area with water and squeegee off excess.

### **Note: On large areas**

use of rotary cleaning machines with dispenser tanks and polypropylene bristle brushes is appropriate. However, brushes should not be worn to the point they are short and/or stiff.

Short, stiff brushes will cause damage to the teak and caulking.

### **Warranty:**

**TDC Liquid** will perform as specified when directions are followed. No other warranty is expressed or implied. Liability limited to purchase price only.