

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** TIKAL Fast Patch Light Epoxi-Spachtel A
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Knife filler/ Surfacers
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Tikal Marine Systemys GmbH
Werkstr. 6
22844 Norderstedt, Germany
Tel: +49 / (0) 40 / 526 30 60 3
Mail: info@tikal-online.de
- **1.4 Emergency telephone number:** + 49 (0) 40 / 526 30 60 3 (Mo-Fr 08:00am to 16:00pm)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS05



GHS07



GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:**
1,4-bis(2,3-epoxypropoxy)butane
Bis[4-(2,3-epoxypropoxy)phenyl]propane
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane
- **Hazard statements**
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

Trade name: TIKAL Fast Patch Light Epoxi-Spachtel A

(Contd. of page 1)

*H411 Toxic to aquatic life with long lasting effects.***Precautionary statements***P261 Avoid breathing dust/fume/gas/mist/vapours/spray.**P280 Wear protective gloves / eye protection / face protection.**P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P310 Immediately call a POISON CENTER/doctor.**P321 Specific treatment (see on this label).**P362+P364 Take off contaminated clothing and wash it before reuse.***Additional information:***EUH205 Contains epoxy constituents. May produce an allergic reaction.***2.3 Other hazards****Results of PBT and vPvB assessment***PBT: Not applicable.**vPvB: Not applicable.***SECTION 3: Composition/information on ingredients****3.2 Mixtures***Description: Mixture of substances listed below with nonhazardous additions.***Dangerous components:**

CAS: 1675-54-3 EINECS: 216-823-5 Reg.nr.: 01-2119456619-26	Bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	25-50%
Reg.nr.: 01-2119454392-40	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<25%
CAS: 2425-79-8 EINECS: 219-371-7 Reg.nr.: 01-2119494060-45	1,4-bis(2,3-epoxypropoxy)butane ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥10-<25%

*Additional information: For the wording of the listed hazard phrases refer to section 16.***SECTION 4: First aid measures****4.1 Description of first aid measures***General information: Immediately remove any clothing soiled by the product.***After inhalation:***Supply fresh air and to be sure call for a doctor.**In case of unconsciousness place patient stably in side position for transportation.***After skin contact: Immediately rinse with water.***After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing: If symptoms persist consult doctor.**4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.***4.3 Indication of any immediate medical attention and special treatment needed***No further relevant information available.*

GB

(Contd. on page 3)

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

Trade name: TIKAL Fast Patch Light Epoxi-Spachtel A

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

Trade name: TIKAL Fast Patch Light Epoxi-Spachtel A

(Contd. of page 3)

*Immediately remove all soiled and contaminated clothing**Wash hands before breaks and at the end of work.**Avoid contact with the eyes.**Avoid contact with the eyes and skin.***· Respiratory protection:***In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.***· Hand protection***Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation**Protective gloves (EN 374)**The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.***· Material of gloves***The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.***· Breakthrough time of glove material***The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.***· Eye/face protection***Tightly sealed goggles***SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Physical state***Liquid***· Colour:***According to product specification***· Odour:***Characteristic***· Odour threshold:***Not determined.***· Melting point/freezing point:***Undetermined.***· Boiling point or initial boiling point and boiling range***294 °C (2425-79-8 1,4-bis(2,3-epoxypropoxy)butane)***· Flammability***Not applicable.***· Lower and upper explosion limit****· Lower:***Not determined.***· Upper:***Not determined.***· Flash point:***140 °C (DIN EN ISO 1523:2002)***· Auto-ignition temperature:***>93 °C (DIN 51794, Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane)***· Decomposition temperature:***Not determined.*

(Contd. on page 5)

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

Trade name: TIKAL Fast Patch Light Epoxi-Spachtel A

(Contd. of page 4)

· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	168,000-192,000 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	<0.1 hPa
· Density and/or relative density	
· Density at 20 °C:	0.679 g/cm ³ (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· VOC (EC)	0.00 %
· Solids content (weight-%):	100.0 %
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Possible in traces.

(Contd. on page 6)

GB

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

Trade name: TIKAL Fast Patch Light Epoxi-Spachtel A

(Contd. of page 5)

Nitrogen oxides
Hydrogen chloride (HCl)
Carbon monoxide
Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

2425-79-8 1,4-bis(2,3-epoxypropoxy)butane

Oral	LD50	1,118 mg/kg (rat)
Dermal	LD50	2,150 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

Trade name: TIKAL Fast Patch Light Epoxi-Spachtel A

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information· **14.1 UN number or ID number**· **ADR, IMDG, IATA**

UN3082

· **14.2 UN proper shipping name**· **ADR**


UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenolresins)

· **IMDG**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenolresins), MARINE POLLUTANT

· **IATA**


ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenolresins)

· **14.3 Transport hazard class(es)**· **ADR**· **Class**

9 (M6) Miscellaneous dangerous substances and articles.

· **Label**

9

· **IMDG, IATA**· **Class**

9 Miscellaneous dangerous substances and articles.

· **Label**

9

· **14.4 Packing group**· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**· **Marine pollutant:**

Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **Special marking (IATA):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

· **Hazard identification number (Kemler code):**

90

· **EMS Number:**

F-A,S-F

· **Stowage Category**

A

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**· **ADR**· **Limited quantities (LQ)**

5L

· **Transport category**

3

(Contd. on page 8)

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

Trade name: TIKAL Fast Patch Light Epoxi-Spachtel A

(Contd. of page 7)

· Tunnel restriction code	(-)
· Remarks:	≤ 5l: SV 375 ADR
· IMDG	
· Limited quantities (LQ)	5L
· Remarks:	≤ 5l: 2.10.2.7 IMDG-Code
· IATA	
· Remarks:	≤ 5l: A 197
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOLRESINS), 9, III

SECTION 15: Regulatory information· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Poisons Act**· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category E2** Hazardous to the Aquatic Environment· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 9)

GB

Safety data sheet

according to UK REACH

Printing date 24.09.2025

Version number 2 (replaces version 1)

Revision: 24.09.2025

Trade name: TIKAL Fast Patch Light Epoxi-Spachtel A

(Contd. of page 8)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

GB