

Technical Information

Produkt : **Tikal Teak Cleaner Liquid + Powder Scrub**

Version: 03 / 2026 (This document supercedes all older versions.)

Product description

Teak Cleaner Liquid

Teak Cleaner Liquid is a ready-to-use liquid cleaner for teak, cork, and PVC. It is tough on dirt but gentle on teak and PVC decks. **Teak Cleaner Liquid** brightens teak and gives it a fresh look. It is compatible with the sealant TSCplus and TBJ 30. Overall, the cleaner is quite environmentally friendly, contains no harsh chemicals, and meets MARPOL criteria.

Teak Cleaner Powder Scrub

Unlike the ready-to-use **Teak Cleaner Liquid**, the **Teak Cleaner Powder Scrub** is a granular powder cleaner for teak, cork, and PVC.

This makes the **Teak Cleaner Powder Scrub** very space-saving. Simply spread the granular powder on the deck and then mix with water for highly effective abrasive cleaning. The **Teak Cleaner Powder Scrub** is even more effective against ingrained dirt, yet gentle on teak and PVC decks. It dissolves slowly on the deck, acting first as a sandpaper / polish paste getting more and more fine as its getting dissolved and following brightening the teak and leaving it looking fresh.

It is compatible with the sealants TSCplus and TBJ 30. Overall, the cleaner is quite environmentally friendly, contains no harsh chemicals, and meets MARPOL criteria.

Applications

Teak Cleaner Liquid

Pre-wet the teak deck thoroughly with fresh water. Apply Teak Cleaner Liquid evenly to the wet surface using a sponge, brush or suitable low-pressure spray equipment.

Allow the product to dwell for approximately 5–10 minutes. Do not allow the surface to dry during application. Agitate the surface using a soft to medium stiffness brush, or a white pad, working strictly across the grain to remove dirt, grease and deposits. Rinse thoroughly with copious amounts of fresh water to remove all residues.

Repeat the application if required for heavily contaminated areas.

Teak Cleaner Powder Scrub

Pre-wet the teak deck thoroughly with fresh water. Evenly distribute Teak Cleaner Powder Scrub in its dry, granular form onto the wet surface.

Work the product into the surface using a soft to medium stiffness brush and additional water, always brushing across the grain. The granular composition provides a controlled abrasive effect, making it particularly effective for removing deeply embedded contamination.

Ensure the surface remains wet throughout the application process. The product gradually dissolves and activates during use. After cleaning, rinse thoroughly with copious amounts of fresh water. Repeat the process if necessary.

Restrictions for application

Do not apply in direct sunlight or on very hot surfaces. Elevated temperatures may cause premature drying and reduce cleaning efficiency. Do not allow the product to dry on the surface. Always keep the treated area wet during the entire cleaning process.

Do not use on untreated sensitive materials such as anodized aluminium or other alkali-sensitive surfaces without prior compatibility testing.

Avoid excessive mechanical abrasion (e.g. hard brushes or across the grain), as this may damage the teak surface. Always work along the grain.

Do not use in temperatures below +5°C or above +30°C.

Avoid prolonged contact with adjacent surfaces (e.g. painted, varnished or metal parts), do not allow the material to dry out on this surfaces.

Rinse off in case of accidental exposure.

Test the product on a small, inconspicuous area prior to full application to ensure compatibility with the substrate.

Not suitable for use on sealed or coated wood surfaces (e.g. varnished or oiled teak)

Technical Data

Base:

Liquid

Citric with surfactants for teak.

Powder

carbonate, soap and surfactants for teak

Density Liquid

1.05 g/ml

Application temperature

5°C to 30°C

Test and registrations

MARPOL conform

Storage

Liquid 3 years

Powder 5 years

Packing

Liquid

1 L bottle

5 L canister

PowderScrub

10 Kg pod

Safety

Wear gloves and safety glasses.

Direct contact with the material can irritate the eyes and skin.

For further information, please refer to the safety data sheet!

<https://www.tikal-online.de/downloads/teac-deck/teak-cleaner>

Warranty / Liability

Tikal Marine Systems GmbH guarantees that all products conform to specifications within the minimum shelf-life indicated. All technical information and processing information are based on our experience and our tests. **Tikal Marine Systems GmbH** also assumes no liability for processing results, as Tikal Marine Systems GmbH has no control over storage, the woods used, the duration of application, the execution or temperatures during processing.